



Justrite Safety Group

457 Skystep™ ESD

ESD rubber mat with moulded edges



457 Skystep™ ESD

Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

Ergonomically and economically engineered, the Skystep™ utilizes the power of air. Skystep™ is designed to suction to the ground to prevent the mat from shifting while trapping air in its chambers. These air pockets combined with the resiliency of the rubber create an ultimate cushioning effect while keeping the mat lightweight.



- Loose lay with no installation required
- Integrated bevelled edges on all four sides to prevent tripping on the mat
- Static dissipative natural rubber compound
- Meets IEC61340-4-1 (category DIF), measured resistance $R_g 10^6 - 10^9 \Omega$, $R_p 10^6 - 10^9 \Omega$

- Dry Areas
- For placement in ESD assembly lines, picking, packing and logistics warehouses, individual workstations for use with static sensitive components or workstations.
- Medium duty

Recommended use



Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

Skystep™ ESD

General

Brand	Notrax
Category	ESD Matting & Accessories
Product Number	457
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skystep™ ESD
Recommended use	For placement in ESD assembly lines, picking, packing and logistics warehouses, individual work stations for use with static sensitive components or workstations.
Series	Skystep™
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Dry Areas - Standalone Rubber Mats
Update trigger	20250520
Usage Intensity	Medium duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty (years)	1

Tests

Abrasion Resistance 1000	0.824
Elongation	210%
Fire rating US	Pass
Hardness	50 Shore A
Slip Rating	R9
Surface Flammability	Pass
Tear Strength	10.5 N/mm

Technical Specifications

Application	Industrial Environments
Breaking Load	4.80 Mpa
Edges	Moulded bevelled edges on all sides
Material	Static dissipative natural rubber
Material Group	Rubber
Process	Compression Moulding

Skystep™ ESD Black

Art. nr.	Art. Nr. Justrite US Ref (ERP)	Dimension (cm)	Weight (kg)	Thickness (mm)
457S0023BL	457S0023BL	60cm x 90cm	5.5	13
457S0035BL	457S0035BL	90cm x 150cm	16	13
457S0034BL	457S0034BL	90cm x 120cm	11.8	13

Accessories



825-C



051

ESD Floor Grounding Cord

4,5 m cable that
connects an ESD mat
to ground.