



Justrite Safety Group

141 - OVATION™
PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax[®] has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax[®] offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax[®] offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**



141 - OVATION™ is made with a generously tufted Decalon® looped pile construction that serves as the finishing, drying and cleaning mat. It can be used as a stand-alone mat, or as the third stage of the “Stages” coordinator entrance matting system. A heavy-weight vinyl non-slip backing ensures minimum movement.

Material: Polypropylene Carpet W/Vinyl Backing

Features and Benefits:

- Drying mat
- Tufted Decalon® looped pile construction for drying and cleaning
- 22 ounces of tufted loop pile yarn per square yard
- Low profile for use in narrow clearance doorways
- Vinyl backing ensures minimal buckling and mat movement
- Can be used as the third section (Drying) of the “Stages” entrance matting system
- Recommended product as part of the GreenTRAX™ program for “Green Cleaning” environments



MODEL: 141

SPECIFICATIONS

APPLICATIONS

- Entranceways
- Lobbies
- Medium traffic areas
- Schools

Stock Sizes	2'x3', 3'x4', 3'x5', 3'x6', 3'x10', 4'x6', 4'x8'		
Roll Sizes	3'x60', 4'x60', 6'x60'		
Thickness	3/8"		
Cut Lengths	3', 4', and 6' widths (up to 60' long)		
Colors	 Burgundy	 Brown	 Grey
	 Black	 Blue	

Performance:

	Good	Better	Best	Superior
Wear Retention	████████████████████			████████
Crush Resistance	████████████████████			████████
Soil Resistance	████████████████████			████████
Function & Appearance	████████████████████			



TESTING DATA

Test	Test Description	Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.8 - Vacuum Rating 5.0 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	243.7 lbs/in ²
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 2.5 Color: 3.0
ASTM D3936-05	Delamination	Exceeds Backing Strength
ASTM D2240-02	Durometer Hardness	75
ASTM D1335-05	Tuft Bind of Pile Yarn	16.3 = Superior
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

*Testing performed by an independent test laboratory.

NOTRAX®

5655 West 73rd Street
Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.