

O/F WAYFARER®







For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- Track record of manufacturing high quality mats for over seventy years
- All products are manufactured in ISO certified facilities
- Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries



# **PRODUCT INFO**

265 - WAYFARER® is a vinyl-loop outdoor mat with a color-coordinated solid-sheet vinyl back. The vinyl-loop design removes dirt and moisture from shoes and securely traps them beneath the mat's surface. Wayfarer® is specially designed to dry quickly and resist mildew making it the perfect mat for outdoor entrances, drinking fountains, and pool areas. Intended for light to medium traffic areas, this flexible mat can be used for industrial, commercial, or residential applications.

## Material: Vinyl

### **Features and Benefits:**

- Vinyl-looped construction traps dirt and moisture while scraping debris
- Color-coordinated thick vinyl backing to resist mat movement
- Factory compressed borders
- Designed to dry quickly and resist mildew
- Recommended product as a part of the GreenTRAX $^{\text{TM}}$  program for "Green Cleaning" environments



MODEL: 265

- **Outdoor Entrances**
- Plant Doorways
- Water Fountain Areas
- Pool Areas

## **SPECIFICATIONS**

Stock Sizes	3'x5', 4'x6'				
Roll Sizes	3'x60', 4'x60'				
Thickness	3/8"				
Cut Lengths	3' and 4' widths (up to 60' long)				
Colors				di Silandi	
	Leaf Green		Brown		Grey
	Black		Navy		
Performance:		Good	Better	Best	Superior
Crush Resistance					
Scraping Performance					













# **TESTING DATA**

Test	Test Description	Results	
ASTM D6540-05	Accelerated Soiling Method	Based on Visual Inspection 2.0 - Vacuum Rating 3.0 - Rating After Extraction	
ASTM D3884	Abrasion Resistance	@ 5,000 cycles 4.84 grams (15.6%)	
-	Accelerated Wear - Sim Floor Machine	Appearance Rating @ 6,000 cycles 5 Appearance Rating @ 12,000 cycles 5	
	Water Retention	Water Weight Gain - 38.0% Water Volume - 0.31 gal/yd2	
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass	

<sup>\*</sup>Testing performed by an independent test laboratory.

# **NOTRAX®**

5655 West 73rd Street Chicago, IL 60638

**PHONE:** (800) 621-2802

**FAX:** (800) 322-7105

**EMAIL:** saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.