

Justrite Safety Group







For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- Track record of manufacturing high quality mats for over seventy years
- All products are manufactured in ISO certified facilities
- Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries



PRODUCT INFO

325 -SMART STEP™ W/ DECALON® alternates rows of ribbed vinyl and carpet strips to scrape and dry foot traffic in entranceways and foyers. This version features cut pile Decalon® carpet matting for a high-end look and functionality in medium to heavy traffic areas. Decalon® fibers provide moisture and dirt retention. Smart Step™ can be placed directly on the floor or fits into most recessed foyers.

Material: Polypropylene Carpet Inset Ribbed Vinyl Tile

Features and Benefits:

- Alternating rows of ribbed vinyl and carpet strips scrape and dry the foot traffic
- 19 ounce per square yard of Decalon® carpet matting strips
- Can be placed within a foyer recess depth of 3/8" to 1/2" allow 9/16" door clearance
- Can also be placed directly on floor allow 9/16" door clearance
- Perforated vinyl sections available to facilitate drainage (recommended for recess areas only)
- Mat is fully assembled at the factory to your custom size specification
- Orders must be accompanied by a sketch clearly indicating width, length and direction of traffic flow
- All mats larger than 12 feet by 22 feet will be made in 2 or more sections
- Vinyl tiles made from 100% recycled PVC.

WARNING: This product can expose you to chemicals including di-2-ethylhexyl phthalate and/or diisononyl phthalate which is known to the State of California to cause cancer, birth defects or reproductive harm For more information, visit www.P65Warnings.ca.gov

MODEL: 325

ATIONS

- Foyers
- Retail
- Shopping Malls
 - Schools

SPECIFICATIONS

Stock Sizes	12"x12" Tiles	
Thickness	9/16"	
Colors	Black	Brown

Performance: Wear Resistance Anti-fatigue Performance Slip Resistance





TESTING DATA

Test	Test Description	Results
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	1.45
Accelerated Soiling ASTM D6540-00	Test specimen is subjected to an accelerated soiling process. for a predetermined length of time. The sample is vacuumed, rated, submitted to an extraction device, then rated again.	(Based on visual inspection) 4 - Vacuum Rating 5 - Rating After Extraction
Water Retention	Test specimen is submerged in water for 5 minutes, removed, drained for 15 seconds and weighed. Results measured in weight gain. (Gallons per sq. yd.)	.39
Flammability ASTM D2859 (CPSC FF 1-70)	Intended to measure the mattings response to an ignition source in a controlled environment. The uncharred area of the test specimen must be greater than 1 inch to pass.	3.5

 $^{{}^{\}star}\text{Testing performed by an independent test laboratory.}$

NOTRAX®

5655 West 73rd Street Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.