

Justrite Safety Group

350 - SOIL GUARDTM W/GRIP-STEPTM PRODUCT INFORMATION BROCHURE







For over 70 years, the name Notrax[®] has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax[®] offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- Track record of manufacturing high quality mats for over seventy years
- Notrax[®] offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries
- All products are manufactured in ISO certified facilities



PRODUCT INFO

350 - SOIL GUARD™ W/GRIP-STEP™ is a durable outdoor entrance mat intended to guard against soil with its high-low scraping design. This mat has silicon carbide grit surface for additional traction. Its low profile allows for easy door clearance as well as regular cart traffic, while a specially formulated rubber allows Slip Guard™ w/Grit-Step™ to withstand harsh weather environments and heavy foot traffic. Slip Guard™ w/Grit-Step™ excels in both indoor and outdoor high traffic entryways and can be hosed off for easy cleaning

Material: Rubber

Features and Benefits:

- Heavy-duty, durable rubber compound.
- Low profile for door clearance / cart traffic
- High-low design scrapes debris from shoe traffic
- Grit surface for added traction
- Easy to clean simply hose off

WARNING: This product can expose you to beryllium which is known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov



MODEL: 350



SPECIFICATIONS

Stock Sizes	3′×5′
Thickness	1/4"
Colors	Black

Performance:

Wear Resistance Water Retention Scraping Performance





TESTING DATA

Test	Test Description	Results
ASTM D3884-01	Abrasion Resistance	2.72 grams (3.5%)
ASTM C1028-96	Static Coefficient of Friction	Wet: 0.79 Dry: 0.84
ASTM D395 ASTM D575 ASTM D1171	Materials Analysis	Compressions Set @ 25%: 0.4% Comp. Deflection @ 25%: 104.0 lbs/in2 Comp. Deflection @ 50% 485.3 lbs/in2 Ozone: Very Slight Cracking
CPSC FF 1-70 ASTM D-2859	Surface Flammability of Carpets and Rugs Ignition Characteristics - Flnished Textile Floor Covering Material	Pass

*Testing performed by an independent test laboratory.

NOTRAX[®] 5655 West 73rd Street Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com





Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.