



Justrite Safety Group

408 - ACHILLES™


PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax[®] has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax[®] offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax[®] offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**




408 - ACHILLES™ is an embossed ribbed top surface that enhances the mats slip resistance while providing increased worker fatigue relief. The PVC closed cell foam construction relieves leg and back discomfort while providing a barrier to cold floors. Achilles™ is intended for applications where basic anti-fatigue relief is required at a low cost.

Material: PVC

Features and Benefits:

- Ribbed textured embossed pattern mat
- Basic anti-fatigue protection provided
- Closed cell PVC foam relieves leg and back discomfort
- Provides an insulated barrier to cold floors
- Beveled edges on all 4 sides of all stock, cuts and rolls
- Max length available up to 120 linear feet (minimum 2 rolls, available in increments of 2)
- Tolerances available upon request





MODEL: 408












SPECIFICATIONS


APPLICATIONS

- Dry Workstations
- Assembly Lines
- Packaging Areas
- Service Counters

Roll Sizes	(3/8" thick) 2'x60', 3'x60', 4'x60' (5/8" thick) 2'x30', 3'x30', 4'x30'
Thickness	3/8", 5/8"
Colors	 Black  Black/Yellow

Performance:

	Good	Better	Best	Superior
Wear Resistance				
Anti-fatigue Performance				
Slip Resistance				



TESTING DATA

Test	Test Description	Results
ASTM C1028-96	Static Coefficient of Friction	Dry: .80
-	Compression Deflection	@ 20 lbs./in2: 0.211 in. @ 40 lbs./in2: 0.269 in.
ASTM D2240-02	Durometer (Shore A)	15
CSPC FF 1-70(ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
ASTM D1004-94a-03	Tear Strength	7.0 lbs.
ASTM D412	Elongation/Tensile	81.5 lbs./in2
ASTM D3884-01	Abrasion Resistance (Measured in % weight loss)	@2500 cycles: (33.62%)

*Testing performed by an independent test laboratory.

NOTRAX®


5655 West 73rd Street
Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.