

Justrite Safety Group

T32 - ULTRA MATTM PRODUCT INFORMATION BROCHURE







For over 70 years, the name Notrax[®] has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax[®] offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- Track record of manufacturing high quality mats for over seventy years
- Notrax[®] offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries
- All products are manufactured in ISO certified facilities



PRODUCT INFO

T32 - ULTRA MAT[™] is a lightweight modular anti-fatigue mat system with molded-in mat connectors for easy on-site custom configurations and longer lengths. An anti-slip surface increases traction in wet or greasy areas and multi-nib backing enhances the ergonomic support of the mat. It's large hole design provides excellent drainage removing liquids and debris from the worker platform and its' lightweight construction makes it easy to handle. Ultra Mat[™] has an available beveled ramp system to reduce trip hazards, allowing for easy access onto and off of the mat.

Material: General Purpose Rubber (Black) and Nitrile Rubber (Red)

Features and Benefits:

- Raised edging around each hole creates a slip resistant surface
- Large drainage holes remove liquid and debris from worker platform
- Modular mat for quick and easy configurations
- Lightweight design for easy handling and cleaning
- Molded-in mat connectors
- Optional rubber ramps available for trip-resistant platform (581 Ramp)
- General Purpose Rubber (Black) 100% Nitrile Grease Resistant (Red)
- Red mat (2 year warranty), Black mat (1 year warranty)



SPECIFICATIONS





MODEL: T32





TESTING DATA

Test	Test Description	Results
ASTM D3884	Abrasion Resistance	@ 1000 cycles: 1.19 grams (2.0%)
ASTM C-1028-96	Static Coefficient of Friction	Wet: 0.62 Dry: 0.63
ASTM D-575	Compression Deflection	@ 25%: 10.1 lbs./in2 @ 50%: 29.3 lbs./in2
ASTM D-1171	Ozone (Method A)	Noticeable Cracking and Color Change
CPSC FF 1-70 ASTM D-2859	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

*Testing performed by an independent test laboratory.

NOTRAX[®] 5655 West 73rd Street Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com





Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.