



Justrite Safety Group

T37 - ATLANTIC OLEFIN™

PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax[®] has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax[®] offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax[®] offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**




T37 - ATLANTIC OLEFIN™ is a step above the commodity entrance mat and is intended for light to medium foot traffic areas including entrances and lobbies. Atlantic Olefin™ durable olefin fibers provide moisture and dirt retention at entrances and passageways; reducing slip hazards and floor care maintenance. A vinyl non-slip backing helps to minimize mat movement.

Material: Polypropylene Carpet W/Vinyl Backing

Features and Benefits:

- Dries shoes and retains debris
- Designed for use in light to medium foot traffic
- Stain resistant, 100% Olefin fibers
- 19 ounces of tufted cut-pile Decalon® per square yard
- Vinyl backing helps reduce mat movement






MODEL: T37

SPECIFICATIONS

Stock Sizes	3'x5', 4'x6'				
Thickness	5/16"				
Colors	 Forest Green	 Dark Toast	 Gun Metal	 Slate Blue	 Crimson

Performance:

	Good	Better	Best	Superior
Water Absorption				
Dirt Scraping				
Wearability				

APPLICATIONS

- Entranceways, lobbies and other indoor light to medium traffic areas



TESTING DATA

Test	Test Description	Results
ASTM D3884-01	Abrasion Resistance	-1.17 grams (3.7%)
ASTM D6540-00	Accelerated Soiling	Based on Visual Inspection 4.0 - Vacuum Rating 5.0 - Rating After Extraction
ASTM D5252-98a	Accelerated Wear	Based on visual inspection @ 4,000 cycles Considerable change in appearance and color
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
*Testing performed by an independent test laboratory.	Water Retention	Weight Gain = 47.7% (0.427 gals./yd ²)

NOTRAX®

5655 West 73rd Street
Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.