



Product Service

CERTIFICATE

No. Z1A 031484 0027 Rev. 00

Holder of Certificate: **Justrite Manufacturing Company L.L.C.**
3921 DeWitt Avenue
Mattoon IL 61938
USA

Certification Mark:



Product: **Waste collectors
Safety Drum Cover**

Tested according to: PPP 53030B:2015

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 034-713229226-000

Valid until: 2028-03-28

Date, 2023-04-13

Horst Kristen

(Horst Kristen)

CERTIFICATE

No. Z1A 031484 0027 Rev. 00

Model(s): 26730, 26750, 26751, 26752, 26753, 26754

Parameters:

Model	Diameter (approx.)	Height (approx.)	Barrel size	Remark
26730	603 mm	127 mm	110 l	Fusible link
26750	724 mm	127 mm	200 l	Fusible link
26752	724 mm	137 mm	200 l	With gasket and vent

Material: Steel plate, powder coated, red. Inside: galvanized steel
Model 26752 equipped with a gasket to prevent the release of odors

Model	Diameter (approx.)	Height (approx.)	Barrel size	Remark
26751	Durchmesser (ca.)	127 mm	200 l	Fusible link

Material: Steel plate, powder coated, yellow. Inside: galvanized steel

Model	Diameter (approx.)	Height (approx.)	Barrel size	Remark
26753	Durchmesser (ca.)	108 mm	200 l	With gasket and vent
26754	Durchmesser (ca.)	156 mm	200 l	With gasket and vent

Material: Steel plate, powder coated, red. Inside: galvanized steel

All types have a fusible link tripping temperature of approx. 74° C.