

Cleaning Tanks, Dipping, Washing

Safety dip tanks are recommended where flammable liquids are used in the coating, cleaning and dipping of small parts. Dip tanks may be obtained in sizes up to 2 ft^2 (0.19 m^2) and are equipped with automatically closing covers actuated by fusible links.

Wash tanks are more convenient than perforated screen type bench cans for washing small parts in quantities. They are available in sizes up to 14 1/2 in. (368 mm) in diameter, and in square or rectangular shape. The perforated basket containing the parts is lowered into the liquid and moved about for a short time. After the washing, the basket is lifted up onto brackets in the can and allowed to drain. Tanks are suitable also for dipping with the basket removed. A fusible link arrangement will close the cover automatically and snuff out fire in the container.

Parts washers are for use only with safety solvents having a flashpoint of 100°F (38°C), TAG closed tester, ASTM D-56-77, or above.

Models 27311, 27322, 27417, 27601, 27602, 27603, 27605, 27606, 27608, 27612, 27615, 27618

Dip Tank. Models 27311, 27322, 27417, 27601, 27602, 27603, 27605, 27606, 27608, 27612, 27615, 27618.

Company Name:	Justrite Mfg Co
Company Address:	3921 Dewitt Ave, Mattoon, Illinois 62938, USA
Company Website:	http://www.justritemfg.com
Listing Country:	United States of America
Certification Type:	FM Approved