

Product Datasheet

Ceiling mounted unheated safety shower

EXP-23G/V
EXP-23GS/V

For areas with limited floor space, this ceiling mounted option is an excellent choice.

Designed in accordance with EN and ANSI standards it is capable of delivering a drenching of water at 76 litres per minute in the event of an emergency. This unheated emergency safety shower is simple to operate using the pull rod for instant activation.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (GS) or galvanised mild steel (G)
OPERATING VALVE	Stainless steel, full bore, stay open ball valve
SHOWER NOZZLE	Injection moulded nylon 6
STANDARD FINISH	Polished brush (GS) or green powder coated (G)
SERVICES	
WATER INLET	1" female BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	76 L per minute / 20 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER/BODY SPRAY	Pull handle
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	150mm (5.9in) x 219mm (8.6in) x 802mm (31.6in)
WEIGHT	5kg (11lb)

General Arrangement Drawing

Ceiling mounted unheated safety shower

EXP-23G/V
EXP-23GS/V

