

Product Datasheet

Unheated safety shower with stainless steel open bowl eye wash

EXP-18G/85G(D)
EXP-18GS/85G(D)

EN and ANSI compliant floor mounted unheated emergency safety shower with stainless steel eye/face wash unit.

For use in indoor applications not subject to the possibility of freezing or overheating.

Fitted with foot pedal as standard.

Delivers 76 litres per minute of potable water from the shower and 12 litres per minute to the eye/face wash.

Available with either galvanised mild steel powder coated (G) or stainless-steel (GS) pipework.



Specifications

MATERIALS OF CONSTRUCTION	
PIPEWORK & FITTINGS	Stainless steel (GS) or galvanised power coated mild steel (G)
OPERATING VALVE	Stainless steel (GS) or nickel plated brass (G) two piece stay open valve
SHOWER NOZZLE	Injection moulded nylon 6
EYE WASH BOWL	Stainless steel
EYE WASH DIFFUSERS	Chrome plated with stainless steel mesh
SERVICES	
WATER INLET	1¼" female BSP
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute
	Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	
MINIMUM	5C / 41F
MAXIMUM	35C / 95F
OPERATION	
SHOWER	Pull handle
EYE WASH	Push plate or foot pedal
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	267mm (10.5in) x 714mm (28.1in) x 2322mm (91.4in)
WEIGHT	16kg (35lb)

General Arrangement Drawing

Unheated safety shower with stainless steel open bowl eye wash

EXP-18G/85G(D)

EXP-18GS/85G(D)

