

Product Datasheet

Optiwash® with removable insulated, or heated and insulated jacket

The OptiWash® 38 litre, wall-mounted, self-contained gravity-fed eye wash supplied with either a thermally insulated jacket or a trace tape heated jacket designed to protect the water temperature in outdoor conditions — helping prevent overheating in direct sunlight or freezing in cold climates. Meets EN and ANSI standards.

Also available with ATEX approved heating



II 2G IIA & IIB T3 X
II 2D IIIC T135 X

Heated jackets supplied with a wall mounted ATEX approved junction box for client's electrical connection.

Voltage 230V - 110V available upon request



Specifications - Optiwash®

MATERIALS OF CONSTRUCTION	
BODY & DELIVERY MANIFOLD	High Density Polyethylene
SPRAY HEADS	Polypropylene
STANDARD FINISH	High visibility orange
SERVICES	
CAPACITY	38 L / 10 US gal
FLOW RATES	1.5 L per minute / 0.4 US gal per minute
OPERATION	
EYE/FACE WASH	Pull down manifold
DIMENSIONS & WEIGHT	
DIMENSIONS (WxDxH)	450mm (18in) x 186mm (7.3in) x 774mm (30in)
WEIGHT	Empty: 5.8kg / 13lb empty. Full: 42kg / 93lb

Specifications - Jackets

MATERIALS OF CONSTRUCTION	
OUTER FABRIC	PE560, grey and green PVC coated polyester
INSULATION	12mm needle felt
INNER FABRIC	Silicone coated glass cloth
FASTENINGS	FR hook and loop with draw cord
DOCUMENT POUCH	Zipped A4
DIMENSIONS - ASSEMBLED (WxDxH)	530mm (20.9in) x 209mm (8.2in) x 785mm (30.9in)
DIMENSIONS - PACKAGED (WxDxH)	508mm (20in) x 102mm (4in) x 762mm (30in)
ELECTRICAL - HEATED JACKET ONLY	
VOLTAGE	230V (110V available upon request)
POWER RATING	60W
HEAT SOURCE	Self-regulating trace tape heating
POWER CONNECTION	Cable entry size M20 x 1.5